

# WD-40 Aerosol

**Hazard Alert Code:**  
**MODERATE**

Chemwatch Material Safety Data Sheet

Version No: 12

Chemwatch 1950-6

Issue Date: 29-Jun-2010

CD 2011/1

NC317TCP

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME**

WD-40 Aerosol

**PROPER SHIPPING NAME**

AEROSOLS

**PRODUCT NUMBERS**

49635

**PRODUCT USE**

■ The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. Application is by spray atomisation from a hand held aerosol pack. Lubricates, corrosion inhibitor, displaces moisture, penetrant, cleans (spray).

**SUPPLIER**

Company: WD-40 Company Australia Pty Ltd

Address:

Level 2, Suite 23, 41 Rawson Street

Epping

NSW, 2121

Australia

Telephone: +61 2 9868 2200

Fax: +61 2 9869 7512

## Section 2 - HAZARDS IDENTIFICATION

**STATEMENT OF HAZARDOUS NATURE****HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to NOHSC Criteria, and ADG Code.****CHEMWATCH HAZARD RATINGS**

	Min	Max
Flammability:	2	
Toxicity:	2	
Body Contact:	2	
Reactivity:	1	
Chronic:	2	

Min/Nil=0  
Low=1  
Moderate=2  
High=3  
Extreme=4

**POISONS SCHEDULE**

None

**RISK**

- Flammable.
- Irritating to skin.
- Risk of explosion if heated under confinement.
- Repeated exposure may cause skin dryness and cracking.
- Vapours may cause drowsiness and dizziness.

**SAFETY**

- Avoid contact with skin.
- To clean the floor and all objects contaminated by this material, use water and detergent.
- If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre (show this container or label).
- This material and its container must be disposed of as hazardous waste.

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
<a href="#">white spirit</a>	8052-41-3.	45-50
<a href="#">paraffinic distillate, heavy, solvent-dewaxed (severe)</a>	64742-65-0.	15-25^
<a href="#">isoparaffins petroleum hydrotreated HFP</a>	64742-47-8.	12-18^
<a href="#">carbon dioxide</a>	124-38-9	2-3^

# WD-40 Aerosol

**Hazard Alert Code:**  
**MODERATE**

Chemwatch Material Safety Data Sheet

Version No: 12

Chemwatch 1950-6

Issue Date: 29-Jun-2010

CD 2011/1

NC317TCP

## Section 4 - FIRST AID MEASURES

### SWALLOWED

- 
- Avoid giving milk or oils.
- Avoid giving alcohol.
- Not considered a normal route of entry.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

### EYE

- If aerosols come in contact with the eyes:
  - Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.
  - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
  - Transport to hospital or doctor without delay.
  - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

### SKIN

- If solids or aerosol mists are deposited upon the skin:
  - Flush skin and hair with running water (and soap if available).
  - Remove any adhering solids with industrial skin cleansing cream.
  - DO NOT use solvents.
  - Seek medical attention in the event of irritation.

### INHALED

- If aerosols, fumes or combustion products are inhaled:
  - Remove to fresh air.
  - Lay patient down. Keep warm and rested.
  - Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
  - If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
  - Transport to hospital, or doctor.

### NOTES TO PHYSICIAN

- Treat symptomatically.
- For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:
- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
  - Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO<sub>2</sub> 50 mm Hg) should be intubated.
  - Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
  - A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
  - Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
  - Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology]

## Section 5 - FIRE FIGHTING MEASURES

### EXTINGUISHING MEDIA

- SMALL FIRE:
  - Water spray, dry chemical or CO<sub>2</sub>
- LARGE FIRE:

- Water spray or fog.

### FIRE FIGHTING

- 
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- If safe, switch off electrical equipment until vapour fire hazard removed.

# WD-40 Aerosol

**Hazard Alert Code:**  
**MODERATE**

Chemwatch Material Safety Data Sheet

Version No: 12

Chemwatch 1950-6

Issue Date: 29-Jun-2010

CD 2011/1

NC317TCP

- Use water delivered as a fine spray to control fire and cool adjacent area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

## **FIRE/EXPLOSION HAZARD**

- - Liquid and vapour are flammable.
  - Moderate fire hazard when exposed to heat or flame.
  - Vapour forms an explosive mixture with air.
  - Moderate explosion hazard when exposed to heat or flame.
  - Vapour may travel a considerable distance to source of ignition.
  - Heating may cause expansion or decomposition leading to violent rupture of containers.
  - Aerosol cans may explode on exposure to naked flame.
  - Rupturing containers may rocket and scatter burning materials.
  - Hazards may not be restricted to pressure effects.
  - May emit acrid, poisonous or corrosive fumes.
  - On combustion, may emit toxic fumes of carbon monoxide (CO).
- Combustion products include: carbon dioxide (CO<sub>2</sub>), phosphorus oxides (PO<sub>x</sub>), sulfur oxides (SO<sub>x</sub>), other pyrolysis products typical of burning organic material.
- Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

## **FIRE INCOMPATIBILITY**

- 
- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

## **HAZCHEM**

(1) NOT APPLICABLE TO THE CARRIAGE OF DANGEROUS GOODS UNDER RID OR ADR

## **Personal Protective Equipment**

Breathing apparatus.

Gas tight chemical resistant suit.

Limit exposure duration to 1 BA set 30 mins.

## **Section 6 - ACCIDENTAL RELEASE MEASURES**

### **MINOR SPILLS**

- 
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Wear protective clothing, impervious gloves and safety glasses.
- Shut off all possible sources of ignition and increase ventilation.
- Wipe up.
- If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated.
- Undamaged cans should be gathered and stowed safely.

### **MAJOR SPILLS**

- 
- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses.
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse / absorb vapour.
- Absorb or cover spill with sand, earth, inert materials or vermiculite.
- If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated.
- Undamaged cans should be gathered and stowed safely.
- Collect residues and seal in labelled drums for disposal.

## **PROTECTIVE ACTIONS FOR SPILL**

From IERG (Canada/Australia)

# WD-40 Aerosol

**Hazard Alert Code:**  
**MODERATE**

Chemwatch Material Safety Data Sheet


Version No: 12

Chemwatch 1950-6

Issue Date: 29-Jun-2010

CD 2011/1

NC317TCP



Isolation Distance	-
Downwind Protection Distance	8 metres
IERG Number	49

From US Emergency Response Guide 2000 Guide 126

## FOOTNOTES

- 1 PROTECTIVE ACTION ZONE is defined as the area in which people are at risk of harmful exposure. This zone assumes that random changes in wind direction confines the vapour plume to an area within 30 degrees on either side of the predominant wind direction, resulting in a crosswind protective action distance equal to the downwind protective action distance.
- 2 PROTECTIVE ACTIONS should be initiated to the extent possible, beginning with those closest to the spill and working away from the site in the downwind direction. Within the protective action zone a level of vapour concentration may exist resulting in nearly all unprotected persons becoming incapacitated and unable to take protective action and/or incurring serious or irreversible health effects.
- 3 INITIAL ISOLATION ZONE is determined as an area, including upwind of the incident, within which a high probability of localised wind reversal may expose nearly all persons without appropriate protection to life-threatening concentrations of the material.
- 4 SMALL SPILLS involve a leaking package of 200 litres (55 US gallons) or less, such as a drum (jerrican or box with inner containers). Larger packages leaking less than 200 litres and compressed gas leaking from a small cylinder are also considered "small spills". LARGE SPILLS involve many small leaking packages or a leaking package of greater than 200 litres, such as a cargo tank, portable tank or a "one-tonne" compressed gas cylinder.
- 5 Guide 126 is taken from the US DOT emergency response guide book.
- 6 IERG information is derived from CANUTEC - Transport Canada.

**Personal Protective Equipment advice is contained in Section 8 of the MSDS.**

## Section 7 - HANDLING AND STORAGE

### PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- DO NOT incinerate or puncture aerosol cans.
- DO NOT spray directly on humans, exposed food or food utensils.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

### SUITABLE CONTAINER

- Aerosol dispenser.
- Check that containers are clearly labelled.

### STORAGE INCOMPATIBILITY

- Avoid reaction with oxidising agents

### STORAGE REQUIREMENTS

- Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can
- Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.

# WD-40 Aerosol

**Hazard Alert Code:**  
**MODERATE**

Chemwatch Material Safety Data Sheet

Version No: 12


Chemwatch 1950-6

Issue Date: 29-Jun-2010

CD 2011/1

NC317TCP

- No smoking, naked lights, heat or ignition sources.
- Keep containers securely sealed. Contents under pressure.
- Store away from incompatible materials.
- Store in a cool, dry, well ventilated area.
- Avoid storage at temperatures higher than 40 deg C.
- Store in an upright position.
- Protect containers against physical damage.
- Check regularly for spills and leaks.
- Observe manufacturer's storing and handling recommendations.

**SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS***X: Must not be stored together**O: May be stored together with specific precautions**+: May be stored together***Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION****EXPOSURE CONTROLS**

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>	Peak ppm	Peak mg/m <sup>3</sup>	TWA F/CC	Notes
Australia Exposure Standards	white spirit (White spirits)		790						(see Chapter 16)
Australia Exposure Standards	white spirit (Petrol (gasoline))		900						(see Chapter 16)
Australia Exposure Standards	carbon dioxide (Carbon dioxide in coal mines)	12500	22500	30000	54000				
Australia Exposure Standards	carbon dioxide (Carbon dioxide)	5000	9000	30000	54000				

**EMERGENCY EXPOSURE LIMITS**

Material	Revised IDLH Value (mg/m <sup>3</sup> )	Revised IDLH Value (ppm)
white spirit 20342	20,000	
white spirit	1	1,000 [LEL]
white spirit	1	1,100 [LEL]

**NOTES**

Values marked LEL indicate that the IDLH was based on 10% of the lower explosive limit for safety considerations even though the relevant toxicological data indicated that irreversible health effects or impairment of escape existed only at higher concentrations.

**MATERIAL DATA**

WD-40 AEROSOL:

Not available

WHITE SPIRIT:

- Odour Threshold Value: 34 ppm (detection), 97 ppm (recognition)

NOTE: Detector tubes for benzene, measuring in excess of 0.5 ppm, are commercially available. The relative quality of epidemiological data and quantitative health risk assessments related to documented and theoretical leukaemic deaths constitute the basis of the TLV-recommendation.

One study [Dow Chemical] demonstrates a significant fourfold increase in myelogenous leukaemia for workers exposed to average benzene concentrations of about 5 ppm for an average of 9 years and that 2 out of four individuals in the study who died from leukaemia were characterised as having been exposed to average benzene levels below 2 ppm. Based on such findings the estimated risk of leukaemia in workers exposed to daily benzene concentrations of 10 ppm for 40 years is 155 times that of unexposed workers; at 1 ppm the risk falls to 1.7 times whilst at 0.1 ppm the risk is about the same in the two groups. A revision of the TLV-TWA to 0.1 ppm was proposed in 1990 but this has been revised upwards as result of industry initiatives.

Typical toxicities displayed following inhalation:

- At 25 ppm (8 hours): no effect
- 50-150 ppm: signs of intoxication within 5 hours
- 500-1500 ppm: signs of intoxication within 1 hour
- 7500 ppm: severe intoxication within 30-60 minutes
- 20000 ppm: fatal within 5-10 minutes

Some jurisdictions require that health surveillance be conducted on occupationally exposed workers. Some surveillance should emphasise (i) demography, occupational and medical history and health advice (ii) baseline blood sample for haematological profile

# WD-40 Aerosol

**Hazard Alert Code:**  
**MODERATE**

Chemwatch Material Safety Data Sheet

Version No: 12

Chemwatch 1950-6

Issue Date: 29-Jun-2010

CD 2011/1

NC317TCP

(iii) records of personal exposure.  
Odour threshold: 0.25 ppm.

The TLV-TWA is protective against ocular and upper respiratory tract irritation and is recommended for bulk handling of gasoline based on calculations of hydrocarbon content of gasoline vapour. A STEL is recommended to prevent mucous membrane and ocular irritation and prevention of acute depression of the central nervous system. Because of the wide variation in molecular weights of its components, the conversion of ppm to mg/m<sup>3</sup> is approximate. Sweden recommends hexane type limits of 100 ppm and heptane and octane type limits of 300 ppm. Germany does not assign a value because of the widely differing compositions and resultant differences in toxic properties.

Odour Safety Factor (OSF)  
OSF=0.042 (gasoline).

For white spirit:

Low and high odour thresholds of 5.25 and 157.5 mg/m<sup>3</sup>, respectively, were considered to provide a rather useful index of odour as a warning property.

The TLV-TWA is calculated from data on the toxicities of the major ingredients and is intended to minimise the potential for irritative and narcotic effects, polyneuropathy and kidney damage produced by vapours.

The NIOSH (USA) REL-TWA of 60 ppm is the same for all refined petroleum solvents. NIOSH published an occupational "action level" of 350 mg/m<sup>3</sup> for exposure to Stoddard solvent, assuming a 10-hour work shift and a 40-hour work-week. The NIOSH-REL ceiling of 1800 mg/m<sup>3</sup> was established to protect workers from short-term effects that might produce vertigo or other adverse effects which might increase the risk of occupational accidents. Combined (gross) percutaneous absorption and inhalation exposure (at concentrations associated with nausea) are thought, by some, to be responsible for the development of frank hepatic toxicity and jaundice.

Odour Safety Factor (OSF)  
OSF=0.042 (white spirit).

## PERSONAL PROTECTION



### EYE

■ No special equipment for minor exposure i.e. when handling small quantities.

OTHERWISE: For potentially moderate or heavy exposures:

- Safety glasses with side shields.

● NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.

### HANDS/FEET

■

- No special equipment needed when handling small quantities.
- OTHERWISE:
- For potentially moderate exposures:
- Wear general protective gloves, eg. light weight rubber gloves.
- For potentially heavy exposures:
- Wear chemical protective gloves, eg. PVC. and safety footwear.

### OTHER

■

- The clothing worn by process operators insulated from earth may develop static charges far higher (up to 100 times) than the minimum ignition energies for various flammable gas-air mixtures. This holds true for a wide range of clothing materials including cotton.
- Avoid dangerous levels of charge by ensuring a low resistivity of the surface material worn outermost.

BRETHERRICK: Handbook of Reactive Chemical Hazards.

No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- Skin cleansing cream.
- Eyewash unit.
- Do not spray on hot surfaces.

### RESPIRATOR

■ Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half-face Respirator	Full-Face Respirator
1000	10	A-AUS P	-
1000	50	-	A-AUS P
5000	50	Airline *	-
5000	100	-	A-2 P
10000	100	-	A-3 P
	100+		Airline**

\* - Continuous Flow \*\* - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

# WD-40 Aerosol

**Hazard Alert Code:**  
**MODERATE**

Chemwatch Material Safety Data Sheet

Version No: 12

Chemwatch 1950-6

Issue Date: 29-Jun-2010

CD 2011/1

NC317TCP

For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

## ENGINEERING CONTROLS

■ General exhaust is adequate under normal conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection.

Provide adequate ventilation in warehouse or closed storage areas.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Speed:
aerosols, (released at low velocity into zone of active generation)	0.5-1 m/s
direct spray, spray painting in shallow booths, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### APPEARANCE

Cloudy light amber flammable liquid with a sweet solvent odour; floats on water. Supplied as an aerosol pack. Contents under PRESSURE. Contains carbon dioxide propellant.

### PHYSICAL PROPERTIES

Liquid.

Gas.

Does not mix with water.

Floats on water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	Not Available	Solubility in water (g/L)	Immiscible
Flash Point (°C)	55 (TCC)	pH (1% solution)	Not Applicable
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	724 max @21C
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	0.82
Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	>1
Volatile Component (%vol)	78	Evaporation Rate	Not Available

## Section 10 - CHEMICAL STABILITY

# WD-40 Aerosol

**Hazard Alert Code:**  
**MODERATE**

Chemwatch Material Safety Data Sheet

Version No: 12

Chemwatch 1950-6

Issue Date: 29-Jun-2010

CD 2011/1

NC317TCP

## CONDITIONS CONTRIBUTING TO INSTABILITY

- 
- Elevated temperatures.
- Presence of open flame.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

## Section 11 - TOXICOLOGICAL INFORMATION

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

##### SWALLOWED

- Accidental ingestion of the material may be damaging to the health of the individual.
- Not normally a hazard due to physical form of product.  
Considered an unlikely route of entry in commercial/industrial environments.

##### EYE

- There is some evidence to suggest that this material can cause eye irritation and damage in some persons.

##### SKIN

- Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.
- Spray mist may produce discomfort.  
The material may accentuate any pre-existing dermatitis condition.  
Open cuts, abraded or irritated skin should not be exposed to this material.

##### INHALED

- Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.
- Inhalation hazard is increased at higher temperatures.  
WARNING: Intentional misuse by concentrating/inhaling contents may be lethal.

### CHRONIC HEALTH EFFECTS

- Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.
- Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS].  
Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin. Chronic exposure to lighter hydrocarbons can cause nerve damage, peripheral neuropathy, bone marrow dysfunction and psychiatric disorders as well as damage the liver and kidneys.  
WARNING: Aerosol containers may present pressure related hazards.

### TOXICITY AND IRRITATION

#### WD-40 AEROSOL:

- Not available. Refer to individual constituents.

#### WHITE SPIRIT:

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

##### TOXICITY

Inhalation (human) TCl<sub>0</sub>: 600 mg/m<sup>3</sup>/8h

Oral (rat) LD50: &gt;5000 mg/kg

Inhalation (rat) LC50: >5500 mg/m<sup>3</sup>/4h

##### IRRITATION

Nil Reported

Eye (human): 470 ppm/15m

Eye (rabbit): 500 mg/24h Moderate

#### ■ for petroleum:

This product contains benzene which is known to cause acute myeloid leukaemia and n-hexane which has been shown to metabolize to compounds which are neuropathic.

This product contains toluene. There are indications from animal studies that prolonged exposure to high concentrations of toluene may lead to hearing loss.

This product contains ethyl benzene and naphthalene from which there is evidence of tumours in rodents

Carcinogenicity: Inhalation exposure to mice causes liver tumours, which are not considered relevant to humans. Inhalation exposure to rats causes kidney tumours which are not considered relevant to humans.

Mutagenicity: There is a large database of mutagenicity studies on gasoline and gasoline blending streams, which use a wide variety of endpoints and give predominantly negative results. All in vivo studies in animals and recent studies in exposed humans (e.g. petrol service station attendants) have shown negative results in mutagenicity assays.

Reproductive Toxicity: Repeated exposure of pregnant rats to high concentrations of toluene (around or exceeding 1000 ppm) can cause developmental effects, such as lower birth weight and developmental neurotoxicity, on the foetus. However, in a two-generation reproductive study in rats exposed to gasoline vapour condensate, no adverse effects on the foetus were observed.

Human Effects: Prolonged/ repeated contact may cause defatting of the skin which can lead to dermatitis and may make the skin more susceptible to irritation and penetration by other materials.

Lifetime exposure of rodents to gasoline produces carcinogenicity although the relevance to humans has been questioned. Gasoline induces kidney cancer in male rats as a consequence of accumulation of the alpha2-microglobulin protein in hyaline droplets in the male (but not female) rat kidney. Such abnormal accumulation represents lysosomal overload and leads to chronic renal tubular cell degeneration, accumulation of cell debris, mineralisation of renal medullary tubules and necrosis. A sustained regenerative proliferation occurs in epithelial cells with subsequent neoplastic transformation with continued exposure. The alpha2-microglobulin is produced under the influence of hormonal controls in male rats but not in females and, more importantly, not in humans.

# WD-40 Aerosol

**Hazard Alert Code:**  
**MODERATE**

Chemwatch Material Safety Data Sheet

Version No: 12

Chemwatch 1950-6

Issue Date: 29-Jun-2010

CD 2011/1

NC317TCP

white spirit, as CAS RN 8052-41-3

**CARCINOGEN**

Crude oil International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs

Group 3

## Section 12 - ECOLOGICAL INFORMATION

**WHITE SPIRIT:****■ For petroleum derivatives:**

Chemical analysis for all individual compounds in a petroleum bulk product released to the environment is generally unrealistic due to the complexity of these mixtures and the laboratory expense. Determining the chemical composition of a petroleum release is further complicated by hydrodynamic, abiotic, and biotic processes that act on the release to change the chemical character.

The longer the release is exposed to the environment, the greater the change in chemical character and the harder it is to obtain accurate analytical results reflecting the identity of the release. After extensive weathering, detailed knowledge of the original bulk product is often less valuable than current site-specific information on a more focused set of hydrocarbon components. Health assessment efforts are frequently frustrated by three primary problems: (1) the inability to identify and quantify the individual compounds released to the environment as a consequence of a petroleum spill; (2) the lack of information characterizing the fate of the individual compounds in petroleum mixtures; and (3) the lack of specific health guidance values for the majority of chemicals present in petroleum products. To define the public health implications associated with exposure to petroleum hydrocarbons, it is necessary to have a basic understanding of petroleum properties, compositions, and the physical, chemical, biological, and toxicological properties of the compounds most often identified as the key chemicals of concern.

**Environmental fate:**

Petroleum products released to the environment migrate through soil via two general pathways: (1) as bulk oil flow infiltrating the soil under the forces of gravity and capillary action, and (2) as individual compounds separating from the bulk petroleum mixture and dissolving in air or water. When bulk oil flow occurs, it results in little or no separation of the individual compounds from the product mixture and the infiltration rate is usually fast relative to the dissolution rate. Many compounds that are insoluble and immobile in water are soluble in bulk oil and will migrate along with the bulk oil flow. Factors affecting the rate of bulk oil infiltration include soil moisture content, vegetation, terrain, climate, rate of release (e.g., catastrophic versus slow leakage), soil particle size (e.g., sand versus clay), and oil viscosity (e.g., gasoline versus motor oil).

As bulk oil migrates through the soil column, a small amount of the product mass is retained by soil particles. The bulk product retained by the soil particles is known as "residual saturation".

Depending upon the persistence of the bulk oil, residual saturation can potentially reside in the soil for years. Residual saturation is important as it determines the degree of soil contamination and can act as a continuing source of contamination for individual compounds to separate from the bulk product and migrate independently in air or groundwater. Residual saturation is important as it determines the degree of soil contamination and can act as a continuing source of contamination for individual compounds to separate from the bulk product and migrate independently in air or groundwater. When the amount of product released to the environment is small relative to the volume of available soil, all of the product is converted to residual saturation and downward migration of the bulk product usually ceases prior to affecting groundwater resources. Adverse impacts to groundwater may still occur if rain water infiltrates through soil containing residual saturation and initiates the downward migration of individual compounds. When the amount of product released is large relative to the volume of available soil, the downward migration of bulk product ceases as water-saturated pore spaces are encountered. If the density of the bulk product is less than that of water, the product tends to "float" along the interface between the water saturated and unsaturated zones and spread horizontally in a pancake-like layer, usually in the direction of groundwater flow. Almost all motor and heating oils are less dense than water. If the density of the bulk product is greater than that of water, the product will continue to migrate downward through the water table aquifer under the continued influence of gravity. Downward migration ceases when the product is converted to residual saturation or when an impermeable surface is encountered.

As the bulk product migrates through the soil column, individual compounds may separate from the mixture and migrate independently. Chemical transport properties such as volatility, solubility, and sorption potential are often used to evaluate and predict which compounds will likely separate from the mixture. Since petroleum products are complex mixtures of hundreds of compounds, the compounds characterized by relatively high vapor pressures tend to volatilise and enter the vapor phase. The exact composition of these vapors depends on the composition of the original product. Using gasoline as an example, compounds such as butane, propane, benzene, toluene, ethylbenzene and xylene are preferentially volatilised. Because volatility represents transfer of the compound from the product or liquid phase to the air phase, it is expected that the concentration of that compound in the product or liquid phase will decrease as the concentration in the air phase increases.

In general, compounds having a vapor pressure in excess of 10-2 mm Hg are more likely to be present in the air phase than in the liquid phase. Compounds characterized by vapor pressures less than 10-7 mm Hg are more likely to be associated with the liquid phase. Compounds possessing vapor pressures that are less than 10-2 mm Hg, but greater than 10-7 mm Hg, will have a tendency to exist in both the air and the liquid phases.

Lighter petroleum products such as gasoline contain constituents with higher water solubility and volatility and lower sorption potential than heavier petroleum products such as fuel oil.

Data compiled from gasoline spills and laboratory studies indicate that these light-fraction hydrocarbons tend to migrate readily through soil, potentially threatening or affecting groundwater supplies. In contrast, petroleum products with heavier molecular weight constituents, such as fuel oil, are generally more persistent in soils, due to their relatively low water solubility and volatility and high sorption capacity. Solubility generally decreases with increasing molecular weight of the hydrocarbon compounds. For compounds having similar molecular weights, the aromatic hydrocarbons are more water soluble and mobile in water than the aliphatic hydrocarbons and branched aliphatics are less water-soluble than straight-chained aliphatics. Aromatic compounds in petroleum fuels may comprise as much as 50% by weight; aromatic compounds in the C6-C13, range made up approximately 95% of the compounds dissolved in water.

Indigenous microbes found in many natural settings (e.g., soils, groundwater, ponds) have been shown to be capable of degrading organic compounds. Unlike other fate processes that disperse contaminants in the environment, biodegradation can eliminate the contaminants without transferring them across media.

The final products of microbial degradation are carbon dioxide, water, and microbial biomass. The rate of hydrocarbon degradation depends on the chemical composition of the product released to the environment as well as site-specific environmental factors. Generally the straight chain hydrocarbons and the aromatics are degraded more readily than the highly branched aliphatic compounds. The n-alkanes, n-alkyl aromatics, and the aromatics in the C10-C22 range are the most readily biodegradable; n-

# WD-40 Aerosol

**Hazard Alert Code:**  
**MODERATE**

Chemwatch Material Safety Data Sheet

Version No: 12

Chemwatch 1950-6

Issue Date: 29-Jun-2010

CD 2011/1

NC317TCP

alkanes, n-alkyl aromatics, and aromatics in the C5-C9 range are biodegradable at low concentrations by some microorganisms, but are generally preferentially removed by volatilisation and thus are unavailable in most environments; n-alkanes in the C1-C4 ranges are biodegradable only by a narrow range of specialized hydrocarbon degraders; and n-alkanes, n-alkyl aromatics, and aromatics above C22 are generally not available to degrading microorganisms. Hydrocarbons with condensed ring structures, such as PAHs with four or more rings, have been shown to be relatively resistant to biodegradation. PAHs with only 2 or 3 rings (e.g., naphthalene, anthracene) are more easily biodegraded. PAHs with only 2 or 3 rings (e.g., naphthalene, anthracene) are more easily biodegraded. A large proportion of the water-soluble fraction of the petroleum product may be degraded as the compounds go into solution. As a result, the remaining product may become enriched in the alicyclics, the highly branched aliphatics, and PAHs with many fused rings.

In almost all cases, the presence of oxygen is essential for effective biodegradation of oil. Anaerobic decomposition of petroleum hydrocarbons leads to extremely low rates of degradation. The ideal pH range to promote biodegradation is close to neutral (6-8). For most species, the optimal pH is slightly alkaline, that is, greater than 7. The moisture content of the contaminated soil will affect biodegradation of oils due to dissolution of the residual compounds, dispersive actions, and the need for microbial metabolism to sustain high activity. The moisture content in soil affects microbial locomotion, solute diffusion, substrate supply, and the removal of metabolic by-products. Biodegradation rates in soils are also affected by the volume of product released to the environment. At concentrations of 0.5% of oil by volume, the degradation rate in soil is fairly independent of oil concentrations. However, as oil concentration rises, the first order degradation rate decreases and the oil degradation half-life increases. Ultimately, when the oil reaches saturation conditions in the soil (i.e., 30-50% oil), biodegradation virtually ceases.

Excessive moisture will limit the gaseous supply of oxygen for enhanced decomposition of petroleum hydrocarbons. Most studies indicate that optimum moisture content is within 50-70% of the water holding capacity.

All biological transformations are affected by temperature. Generally, as the temperature increases, biological activity tends to increase up to a temperature where enzyme denaturation occurs. The presence of oil should increase soil temperature, particularly at the surface. The darker color increases the heat capacity by adsorbing more radiation. The optimal temperature for biodegradation to occur ranges from 18 C to 30 C. Minimum rates would be expected at 5 C or lower.

DO NOT discharge into sewer or waterways.

## Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
WD-40 Aerosol	No Data Available	No Data Available		
white spirit	No Data Available	No Data Available		

## Section 13 - DISPOSAL CONSIDERATIONS

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Consult State Land Waste Management Authority for disposal.
- Discharge contents of damaged aerosol cans at an approved site.
- Allow small quantities to evaporate.
- DO NOT incinerate or puncture aerosol cans.
- Bury residues and emptied aerosol cans at an approved site.

## Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE GAS

**HAZCHEM:**

2YE (ADG7)

Land Transport UNDG:

Class or division	2.1	Subsidiary risk:	None
UN No.:	1950	UN packing group:	None

Shipping Name: AEROSOLS

**Air Transport IATA:**

# WD-40 Aerosol

**Hazard Alert Code:**  
**MODERATE**

Chemwatch Material Safety Data Sheet

Version No: 12

Chemwatch 1950-6

Issue Date: 29-Jun-2010

CD 2011/1

NC317TCP

UN/ID Number:	1950	Packing Group:	-
Special provisions:	A145		
Shipping Name: AEROSOLS, FLAMMABLE			
<b>Maritime Transport IMDG:</b>			
IMDG Class:	2	IMDG Subrisk:	SP63
UN Number:	1950	Packing Group:	None
EMS Number:	F-D , S-U	Special provisions:	63 190 277 327 959
Limited Quantities:	See SP277		
Shipping Name: AEROSOLS			

## Section 15 - REGULATORY INFORMATION

### POISONS SCHEDULE

None

### REGULATIONS

#### Regulations for ingredients

**white spirit (CAS: 8052-41-3) is found on the following regulatory lists;**

"Australia Exposure Standards", "Australia Hazardous Substances", "Australia Inventory of Chemical Substances (AICS)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals"

**No data for WD-40 Aerosol (CW: 1950-6)**

## Section 16 - OTHER INFORMATION

### Ingredients with multiple CAS Nos

Ingredient Name	CAS
isoparaffins petroleum hydrotreated HFP	64742-47-8, 64742-82-1, 8052-41-3, 1030262-12-4, 101795-05-5

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:  
www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: 29-Jun-2010

Print Date: 24-Jun-2011